

शिवराज नगरपालिका नगर कार्यपालिकाको कार्यालय

चन्द्रौटा, कपिलवस्तु लुम्बिनी प्रदेश, नेपाल

पत्र संख्या : २०८०/०८१

चलानी नम्बर :

मिति : २०८०।११।२३

विषय - दररेट पेश गर्ने बारे।

प्रस्तुत विषयमा यस कार्यालयबाट आ.व. २०८०।०८१ को लागि बार्षिक कार्यक्रम अन्तर्गत ब्याक हो लोडर खरिद गर्नु पर्ने भएकोले तपसिलमा उल्लेखित स्फेसिफिकेसन आधारमा ईच्छुक कम्पनि वा डिलर्सहरुले के कित दररेटमा कार्यालयमा उपलब्ध गराउन सिकन्छ सो को विवरण यो सूचना प्रकाशन भएको मितिले ७ दिन भित्र कार्यालय समयमा कार्यालयमा उपलब्ध गराइ दिनु हुन यो सूचना प्रकाशन गरिएको छ।

तपसिल

mic	Backhoe Loader e: श्री शिवयूच नगरप etter no. pa. san.	Technical Specification o :- I(one) Unit tलिका, नगरपालिकाको कार्यालय- चन्द्रोटा,कपिलकारतु. 080/081, Cha. No. 1921, Date 2080/11/04 Bs.	Backnoe Los	ider			
s.N.	Criteria	Requrement			Offered Specification		
1	General	4 Wheel Drive Backhoe Loader suitable or drain cleaning, excavation, pilling etc and and or tough/adverse excavation ground an Ambient Temperature: -5 degree C to Relative Humudity: up to 99%	Make: Model: Country of Origin: Year of Mfg.:				
	Engine	Four Stroke, Turbocharged Engine, Water gross power not less than 90 HP at governe advace technologies and all complete	Make: Model:				
2		Engine Gross Power at rated RPM:	Not Less Than	90	IIP		
		Maximum Torque at rated RPM:	Not Less Than	350	NM.	1	
		Engine Displacement: Cauges and or meters as necessary for en	Not less Than .	4400	cc	Mark The Park I I	
3	Gauges	and satety. Including but not limited to am fuel oil pressure, transmission and dydraul necessary for efficient operation.	v.				
4	Hyraulic System	Hydraulically operated swing system, travel system and work implement systems equipped with suitable capacity and adequate units of hydraulic elyinder, pump/motors, reservoir, sensor and all other necessary devices for efficient operation/control and safety of hydraulic system for a maximum. Main Pump Oil Flow Capacity: [not less than: 125] pm					
		Maximum hydraulic pressure for travel : circuit :	The state of	4.22.49	bar	de Fr	
5	Transmission	Torque converter with synchromesh gear box or as per manufacturer standard of respective equipment with minimum of 4 forward gears and 4 reverse gears.					
F	or Backhoe	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	73.447	1			
		I.Maximum digging/working height:	not less than	5700	ınm		
6		2.Maximum dumping load over/operating height:	not less than	3750	mbi		
	Working	3. Maximum dumping/ loading reach:	not less than	1500	mm		
		4. Maximum digging depth:	nut less than	4500	mm 🗀	The state of	
		5.Maximum reach from swing centre /plvot :	not loss than	5400	mm		
F	or Loader		lunta last th	Lanna			
		1.Dumping height:	note less than	2700			
7	Working	2.Dumping reach at maximum angle:	note less than	3150	mni	11	
		3. Maximum operating height:	note less than	100			
		4, Maximum digging depart	note less than	50	KN		
		5. Break Out Force:	not less than	30	cu.m		
8	Bucket	Tenteo capacity:	inclus than				
9	Operating Weight	Maximum Operating Weight :	not less than	7500	kg		
10	Steering System	Power Steering system with hydraulic or hydrostatic assistance					
11	Brakes	Oil immersed, hydraulically actuated disc i					

फोन नं. ०७६-५४०११८,०७६-५४०१४७, फ्याक्स नं. ०७६-५४०११८

Email: info@shivarajmun.gov.np , shivrajmunicipality@gmail.com,

website: http://shivrajmun.gov.np



शिवराज नगरपालिका नगर कार्यपालिकाको कार्यालय

चन्द्रौटा, कपिलवस्तु लुम्बिनी प्रदेश, नेपाल

पत्र संख्या : २०८०/०८१

चलानी नम्बर :

मिति : २०८०।११।२३

12		Front & Rear : Standard Size	
13	System	Mimimum 12 v. battery system with starter and alternator	
14	Cab/Color	1. The backhoe loader shall be furnished with an operator's cabin. The cabin shall be completely enclosed and equipped with tinted safety glass to provide allroud visibility. Ergonomically designed adjustable operator seat and steering control system. 2. Standard Color	
	Essential Accessories	1.Service hour meter 2.Windereen wiper 3.Working light (front and Rear)	(6.
15		4.Door Lock 5.Side View Mirrors on left and right 6.Fully adjustable crushioned operatro's seat	
		To be equipped with all accessories offered in standard model but not limited to the above items	ing of
16	Instruction	All signs and instruction in the equipment shall be in English	117
17	Mannuais	One copy of the Operators's and Owners Instruction and Maintenance One hard and one soft copy of following manauls in English shall be a.Spare Parts Catalogue	A. Cont
		b.Comprehensive workshop manual	refugles.
18	Tools	A set of tools as required for general maintenance shall be supplied with in-	
19	Warranty	Manufacturer shall provide a minimum of one year warranty after	
	Proven performance	The machine offered shall be a current model under standard production by the manufacturer for at least one year.	
20		2. The bidder shall provide the manufacturer's data of the performance of the unit to include the fuel comsumption, performance curve of the engine and production capacity of the unit.	
21	Initial Service spare parts required for the firt three service, after the equipment has been commissioned and accepted.		
22	The Supplier shall arrange and conduct training by the expert engineers in Related Service the basic maintenance and operation performance at least one day for the operator of Shiveraj Municipality Chandrauta Kaplibastu.		
23	Document evidences and After sales	The bidder is required to submit documentary evidence showing that the manufactur's representative in Nepal has been providing after sales service.	
24	Delivery	The Backhoe Loader I Unit shall be delivered with all necessary to: श्री शिवराज नगरपालिका, नगरपालिकाको कार्यालय- चन्द्रीटा,कपिलबस्तु.	

Note:

The major items are indicated by bold and highlighted letters/alphabets/figures in the technical specifications. Non-compliance of these major items will result in non-responsiveness of the bld offered.

फोन नं. ०७६-५४०११८,०७६-५४०१४७, फ्याक्स नं. ०७६-५४०११८

Email: info@shivarajmun.gov.np, shivrajmunicipality@gmail.com,

website: http://shivrajmun.gov.np

